



PALETLİ PLATFORM

LEO 12T

Paletli Platform

12_m

Çalışma yüksekliği

120_{kg}

Kaldırma kapasitesi

8,45_m

Yatay erişim

2.985_{kg}

Ağırlık

+90 216 999 95 99

info@skyriseplatform.com

skyriseplatform.com

İhlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul



Ürün sayfası

TEUPEN[®]
...access redefined

Specifications


MEASUREMENTS	Metric
Working height, max.	12,00 m
Horizontal outreach, max.	8,45 m
Platform height (A)	1,10 m
Platform length (B)	0,80 m
Platform width (C)	0,70 m
Length, overall (D)	4,75 m
Length without basket (E)	2,80 m
Height, travelling position (F)	1,99 m
Width, min. (G)	1,76 m
Track (L x W) (H)	220 x 25 cm

PRODUCTIVITY	Metric
Basket capacity	120 kg
Movable Jib	-
Turret rotation	220°
Positionable on ground slopes of	2,0°/3,5 %
Height and width track adjustment	-
Gradeability, max.	8,5°/15,0 %
Slope angle	8,5°/15,0 %
Travel speed	1,2 km/h


WEIGHT	Metric
Total weight	2985 kg
Live load in travelling position	4,15 kN/m ²
Live load in working position	4,15 kN/m ²

POWER	
Standard power source	Battery: Atech (24 V, 450 Ah, 4,5 kW)
Optional power sources	1) Electric: 230 V, 12,9 A, 2,2 kW 2) Petrol/gas: Honda GX 390 (9,6 kW/12,8 hp) 3) Diesel: Kubota Z 602 (10,8 kW/14,5 hp)
Fuel tank capacity petrol/gas engines	6,5 l
Fuel tank capacity Diesel engines	13,0 l

LEO12T



WORKING ENVELOPE



STANDARDS COMPLIANCE



EN ISO 9001



Product specifications are subject to change without notice or obligation. Photographs and drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, expressed or implied. Products and services listed may be trademarks, service marks or trade-names of Teupen Maschinenbau GmbH and/or its subsidiaries in the U.S.A. and many other countries. "Teupen", "Access redefined" and "LEO Series" are registered Trademarks of Teupen GmbH in the United States of America and many other countries. Version 2015-A © 2015 Teupen Maschinenbau GmbH.



Features

TRACK CHASSIS

- Powerful track drive for precise maneuvering and terrainability
- Rubber tracks with specially arranged profile providing optimum grip
- White, non-marking rubber tracks
- Chassis designed for an optimal ground pressure

BOOM SYSTEM

- All functions are available from one control panel
- Boom rotation via high-performance slew ring with worm gear and hydraulic-motor
- Detachable basket
- Double swivel for more flexibility at work in facilities
- Compact machine dimensions for an optimal manoeuvrability
- Profile system consists of steel- and aluminium components for better performance parameters and maximum stability

POWER SOURCES

- Battery drive with four 6 V batteries, incl. charging device and indicator lamp

PRODUCTIVITY, SAFETY, QUALITY

- 230 V (EU), 115 V (US) power outlet in the basket
- High-quality paint in RAL 3020 (red)
- Booms made of anodized aluminum
- Hydraulic emergency lowering via hand pump
- Drive operation without basket available
- Biodegradable hydraulic oil
- Protective covers for oil-tank, emergency controls and connecting cables and hoses
- Possible to be lifted in goods elevators
- Easily removable covers for optimal accessibility
- Ergonomically shaped basket with eyelets for safety belts
- Hour meter



OPTIONS

- Honda GX 390 petrol/gas engine (9,6 kW/12,8 hp)
Only one combustion engine can be selected
- Kubota Z 602 Diesel engine (10,8 kW/14,5 hp)
Only one combustion engine can be selected
- Electric drive (230 V, 12,9 A, 2,2 kW)
- Custom paintwork, one colour, according to RAL scheme (except metallic coatings, signal- or special colors)
- Custom paintwork, two colours, according to RAL scheme (except metallic coatings, signal- or special colors)

ACCESSORIES

- Track mat (2000 x 800 x 15 mm/6 ft 6 in x 3 ft 3 in x 1/2 in)
- Safety harness

Enquiries from North & South America:

US Office

Teupen USA, Inc.
10701 Southern Loop Blvd.
Pineville, NC 28134, USA
phone (704) 248-9871
fax (704) 248-9889
infousa@teupen.com
www.teupen.com/us

Enquiries from Europe, Asia, Middle East & Africa:

Corporate Headquarters

Teupen Maschinenbau GmbH
Marie-Curie-Str. 13
48599 Gronau, Germany
phone +49 2562 8161-0
fax +49 2562 8161-888
mail@teupen.com
www.teupen.com

Yükseklerde bizimle güvendesiniz

Makaslı, eklemli, teleskopik, dikey, çekilebilir, paletli ve araçüstü platformlardan oluşan geniş kiralık filo; belgeli ve bakımlı olarak teslim edilir. İhtiyacınıza uygun makineyi birlikte seçelim.

- ✓ Ücretsiz keşif ve makine seçimi
- ✓ Periyodik kontrol ve CE evrakları
- ✓ Operatör eğitimi
- ✓ Türkiye geneli nakliye ve teslimat
- ✓ Kiralama boyunca bakım ve yerinde servis
- ✓ 7/24 saha destek hattı

1.500+

kurumsal müşteri

CE belgeli

kontrollü teslimat

Türkiye geneli

nakliye

7/24

saha desteği

İLETİŞİM

+90 216 999 95 99

WhatsApp +90 536 915 98 11

info@skyriseplatform.com

skyriseplatform.com

İhlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul



Ürün sayfası