

SCISSOR LIFT

SR0818D(SR2669D)

Diesel Scissor Lift

MANUFACTURER · LGMG

+90 216 999 95 99

info@skyriseplatform.com

skyriseplatform.com

İhlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul




Ask on WhatsApp

LGMG

SR0818D

DIESEL RT SCISSOR LIFT

- Larger work platform with high capacity offers great productivity.
- Powerful diesel engine, oscillating axels and four-wheel drive provides better performance on most rough terrain job sites.
- The overload system and motion alarm help the operator to complete the job in a much safer way.
- Pull-out engine tray for easy access and maintenance.
- On-board self-diagnosis system makes it easier for quick troubleshooting.



LGMG DIESEL RT Scissor Lift

SPECIFICATIONS


MODELS	SR0818D (SR2669D)	
Measurements	Metric	Imperial
Work Height Max.	9.7m	31'10"
A Platform Height - Raised	7.7m	25'3"
B Platform Height - Stowed	1.41m	4'8"
C Platform Length	2.79m	9'2"
D Platform Width	1.6m	5'3"
E Overall Length (with ladder)	3.76m	12'4"
F Overall Width	1.79m	5'10"
G Overall Height - Rails up	2.58m	8'6"
Overall Height - Rails down	1.92m	6'4"
H Extension Deck	1.52m	5'
I Wheelbase	2.29m	7'6"
Ground Clearance-Center	0.23m	9"
PRODUCTIVITY		
Max. Platform Occupancy (in/out)	4 / 4	
Platform Capacity	680kg	1,499 lbs
Platform Capacity - Extension	140kg	310 lbs
Drive Height	Full Height	
Gradeability - Stowed	35%	
Min. Turning Radius	4.75m	15'7"
Raise/Lower Speed	35 / 30s	
Brakes	Rear-wheel brake	
Drive Mode	4x4x2	
Tire Type	Foam-filled	
Tire Size	663x283mm	26"x11"
Ground Pressure, Tyres	490.41 kPa	71.1 psi
POWER		
Power Source	Kubota 15.7kw/21.1hp	
Fuel Tank Capacity	53L	14gal
HYDRAULIC SYSTEM		
Hydraulic Oil Volume	50L	13.21gal
WEIGHT		
Machine Weight	4,170kg	9,193 lbs

STANDARD FEATURES

Proportional control	Emergency stop device
Foldable guardrail	Manual brake release
Emergency descent	Tilt alarm with lift cut-out
Oscillating axle	Overload sensing system
Self-lock entry gate	Intelligent diagnostic system
All motions alarm	Descent alarm with flashing beacon
RT Foam-filled tires	AC power to platform

OPTIONAL

Telematics	Solid tires
Cold weather package	Solid non-marking tires
Auto-leveling outriggers	Foam-filled non-marking tires
Biodegradable hydraulic oil	



Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.

LINGONG HEAVY MACHINERY CO., LTD.

Address: No. 2676, Kejia Road, Jinan, Shandong, China
Email: sales@lmg.com.cn Tel: +86 531 6787 9283

LGMG Europe B.V.

Address: Donker Duyvisweg 301, 3316 BL Dordrecht, The Netherlands
Email: sales@lmggeurope.com Tel: +31 850 642 777

LGMG North America Inc.

Address: 4105 Live Oak Drive, Suite 100, The Colony, Texas 75056 United States
Email: sales@lmgna.com Tel: +1 833 288 5464

www.lmglifts.com



RELIABILITY IN ACTION

At height, you're safe with us

A large hire fleet of scissor, articulated, telescopic, vertical mast, trailer-mounted, tracked and truck-mounted platforms, delivered fully documented and well maintained. Let us help you choose the right machine.

- ✓ Free site survey and machine selection
- ✓ Periodic inspection and CE paperwork
- ✓ Operator training
- ✓ Transport and delivery across Türkiye
- ✓ Maintenance and on-site service throughout the hire
- ✓ 24/7 on-site support line

1,500+

corporate clients

CE-marked

inspected delivery

Across Türkiye

transport

24/7

on-site support

CONTACT

+90 216 999 95 99

WhatsApp +90 536 915 98 11

info@skyriseplatform.com

skyriseplatform.com

İhlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul



Ask on WhatsApp