

SCISSOR LIFT

0608N (1930N)

Electric Scissor Lift

MANUFACTURER · SINOBOOM



+90 216 999 95 99

info@skyriseplatform.com

skyriseplatform.com

İhlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul



Ask on WhatsApp

ELECTRIC SCISSOR LIFTS - HYDRAULIC DRIVE

0608N (1930N)

Compliance with CE/ANSI standards

PRODUCT HIGHLIGHTS

Compatible Components

- Components used on Neo series scissor lift are common and compatible with last generation's scissor lift, decreasing total operating cost for rental companies and end users

Safe and Reliable

- Extensively tested and verified Sinoboom control system, function-integrated ECU with wide screen for easy and highly efficient operation. Reliable PCU features high degree of protection, which is collision and crash resistance
- Automobile-grade electrophoretic coating process is applied on the machine, coating is deposited on the surface of the metal to prevent corrosion, and aging of paint while providing a consistent and durable paint finish

Easy Maintenance

- AGM maintenance-free batteries come as standard, long runtime and require less maintenance
- Swing-out trays provide easy access to components, self-diagnosis system and markers on each cable & tube that are benefit to easy and quick maintenance
- Unique bumper rails protect decals and paint well, keeping machine looking like new

Best Productivity

- Front wheel drive and steering provides small turning radius and anti-slip when drive indoors
- Machine can be used both indoor and outdoor, greatly improve work efficiency at work site
- Available options would help get jobs done easily and efficiently



Standard Features		
2WD×2WS	AGM maintenance-free battery	Indoor & outdoor use
Non-marking tires	Proportional control	Fault diagnosis system
Emergency stop	Electrophoretic painting	Emergency lowering system
Flashing beacon	Forklift pockets and lifting points	Tilt protection system
Foldable guardrail	Automatic pothole protection	Overload sensing system
Drivable at full height	Bumper rails	Manual storage box
Horn & buzzer	Telematics-ready connector	Auto braking system
Options & Accessories		
RCBO	AC power to platform	Overhead anti-collision device
Footswitch		

SINOBOOM™

PARTNERS IN ACCESS™

SINOBOOM.COM | SALES@SINOBOOM.COM




NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

ELECTRIC SCISSOR LIFTS - HYDRAULIC DRIVE

0608N (1930N)

Compliance with CE/ANSI standards

Model	0608N (1930N)
Dimensions	
Max Working Height (Indoor/Outdoor)	7.8 m (25'7")
A Max Platform Height (Indoor/Outdoor)	5.8 m (19')
B Platform Extension	0.9 m (3')
C Length-Stowed	1.78 m (5'10.1")
D Width-Stowed	0.79 m (2'7.1")
E Height-stowed (Rails Folded)	1.78 m (5'10.1")
E Height-stowed (Rails Unfolded)	2.15 m (7'0.6")
F Wheelbase	1.325 m (4'4.2")
Ground Clearance (Pothole Guard Stowed)	0.061 m (2.4")
Ground Clearance (Pothole Guard Deployed)	0.03 m (1.2")
Platform Size (L×W×H)	1.64 m×0.76 m×1.1 m (5'4.6"×2'6"×3'7")
Performance	
Platform Capacity	230 kg (507 lbs)
Extension Platform Capacity	120 kg (265 lbs)
Max Platform Occupants (Indoor/Outdoor)	2 Persons / 1 Person
Drive Speed (Stowed)	0 ~ 3 km/h (0 ~ 1.86 mph)
Drive Speed (Raised)	0 ~ 0.5 km/h (0 ~ 0.31 mph)
Lift Time (Unloaded)	15 s~20 s
Lower Time (Unloaded)	25 s~30 s
Gradeability	25%
Max Allowable Inclination (front-to-back/side-to-side)	3° / 1.5°
Turning Radius (Inside/Outside)	0 m/1.49 m (0/4'10.7")
Tire Spec/Type	305×115 mm/solid (12×4.5")
Power	
Drive × Steer	2 WD×2 WS
Power Source (V/kW)	24V DC , 3.3 kW
Hydraulic Tank Capacity	9 L (2.0 gal (UK) /2.4 gal (US))
Batteries	24 V, 220 Ah (AGM maintenance-free battery)
Charger (Input/Output)	100 ~ 240 V AC/30 A
Weight	
Weight	1,550 kg (3,417 lbs)
Standards Compliance	CE/ANSI



We reserve the right to make specification. The above represents the current specifications at time of publications. 10. 2025

At height, you're safe with us

A large hire fleet of scissor, articulated, telescopic, vertical mast, trailer-mounted, tracked and truck-mounted platforms, delivered fully documented and well maintained. Let us help you choose the right machine.

- ✓ Free site survey and machine selection
- ✓ Periodic inspection and CE paperwork
- ✓ Operator training
- ✓ Transport and delivery across Türkiye
- ✓ Maintenance and on-site service throughout the hire
- ✓ 24/7 on-site support line

1,500+

corporate clients

CE-marked

inspected delivery

Across Türkiye

transport

24/7

on-site support

CONTACT

+90 216 999 95 99

WhatsApp +90 536 915 98 11

info@skyriseplatform.com

skyriseplatform.com

İhlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul



Ask on WhatsApp