

SCISSOR LIFT

1018RE (3369RE), 1218RE (4069RE)

Electric Scissor Lift

MANUFACTURER · SINOBOOM



+90 216 999 95 99

info@skyriseplatform.com

skyriseplatform.com

İhlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul



Ask on WhatsApp

ELECTRIC ROUGH TERRAIN SCISSOR LIFTS

1018RE (3369RE) / 1218RE (4069RE)

Compliant with CE/ANSI/EAC standards

PRODUCT HIGHLIGHTS

Excellent Performance

- Up to 35% gradeability, easily handling outdoor needs

High Efficiency

- 1.6m(5'3") wide platform with one-way extension platform
- One-click leveling, easy work on uneven road surfaces

Easy Maintenance

- Two-sided hatchback door design,for convent maintainai
- Self-diagnose sustem display alarm

Green

- Comfortable working environment without noise pollution
- Meet indoor or emissions-critical site requirements

Economical

- Battery quality assurance, low failure rate and reduced maintenance costs compared with diesel power, which reduces overall operating cost



Standard features		
2WD×2WS	Forklift pockets and lifting points	Proportional control
Manual storage box	Flashing beacon	Emergency lowering system
Emergency stop	Electrophoretic painting	Tilt protection system
Foam-filled non-marking tires	Foldable guardrail	Auto braking system
Overload sensing system	Oscillating axle	Fault diagnosis system
Horn & buzzer	Drivable at full height	
Options & Accessories		
AC power cable to platform	Platform work light	Overhead anti-collision device
Telematics-ready connector	7.4m platform	

SINOBOOM™

PARTNERS IN ACCESS™




SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

ELECTRIC ROUGH TERRAIN SCISSOR LIFTS
1018RE (3369RE) / 1218RE (4069RE)

Compliant with CE/ANSI/EAC standards

Model	1018RE (3369RE)	1218RE (4069RE)
Dimensions		
Max Working Height	12 m (39'4.4")	14.2 m (46'7.1")
A Max Platform Height	10 m (32'9.7")	12.2 m (40'0.3")
B Max Horizontal Extension	1.5 m (4'11.1")	1.5 m (4'11")
C Length-Stowed (Outriggers/Without Outriggers)	3.8 m/3.19 m (12'5.6"/10'5.6")	3.8 m/3.19 m (12'5.6"/10'5.6")
D Width-Stowed	1.77 m (5'9.7")	1.77 m (5'9.7")
E Height-stowed (Rail Folded)	1.96 m (6'5.2")	2.11 m (6'11.1")
E Height-stowed (Rail Unfolded)	2.59 m (8'6")	2.75 m (9'0.3")
F Wheelbase	2.28 m (7'5.8")	2.28 m (7'5.8")
Ground Clearance	0.22 m (8.66")	0.22 m (8.66")
Platform Dimensions (L×W×H)	2.8 m×1.6 m×1.1 m (9'2"×5'3"×3'7")	2.8 m×1.6 m×1.1 m (9'2"×5'3"×3'7")
Performance		
Platform Capacity	450 kg (992 lbs)	365 kg (805 lbs)
Extension Platform Capacity	140 kg (309 lbs)	140 kg (309 lbs)
Platform Allowable Occupants (Indoor/Outdoor)	4 persons/2 persons	3 persons/2 persons
Drive Speed (Stowed)	0~6 km/h (0~3.7 mph)	0~6 km/h (0~3.7mph)
Drive Speed (Raised)	0~0.48 km/h (0~0.3 mph)	0~0.48 km/h (0~0.3mph)
Lift Time (Unloaded)	42 s~52 s	55 s~65 s
Lower time (Unloaded)	40 s~50 s	50 s~60 s
Gradeability	35 %	35 %
Tilt Rating (Front to Back)	3°	3°
Tilt Rating (Side to Side, Outrigger Retred/Extend)	2° /0.8°	2° /0.8°
Max Outrigger Leveling (Front to Back)	5.3° (front)/4.2° (back)	5.3° (front)/4.2° (back)
Max Outrigger Leveling (Side to Side)	11.7°	11.7°
Turning Radius (Inside/Outside)	2.11 m/4.6 m (6'11"/15'1")	2.11 m/4.6 m (6'11"/15'1")
Tire Size/Type	26×12-16.5/Solid foam filled	26×12-16.5/Solid foam filled
Power		
Drive × Steer	2 WD×2 WS	2 WD×2 WS
Batteries	48 V, 390 Ah	48 V, 390 Ah
Hydraulic Tank Capacity	72 L (15.8 gal (UK)/19 gal (US))	72 L (15.8 gal (UK)/19 gal (US))
System Voltage	48 VDC	48 VDC
Weight		
Weight (Outriggers/Without Outriggers)	4,510 kg (9,943 lbs) 4,050 kg (8,929 lbs)	5,580 kg (12,302 lbs) 5,110 kg (11,266 lbs)
Standards Compliance	CE/ANSI/EAC	



We reserve the right to make specification. The above represents the current specifications at time of publications. 10. 2025

At height, you're safe with us

A large hire fleet of scissor, articulated, telescopic, vertical mast, trailer-mounted, tracked and truck-mounted platforms, delivered fully documented and well maintained. Let us help you choose the right machine.

- ✓ Free site survey and machine selection
- ✓ Periodic inspection and CE paperwork
- ✓ Operator training
- ✓ Transport and delivery across Türkiye
- ✓ Maintenance and on-site service throughout the hire
- ✓ 24/7 on-site support line

1,500+

corporate clients

CE-marked

inspected delivery

Across Türkiye

transport

24/7

on-site support

CONTACT

+90 216 999 95 99

WhatsApp +90 536 915 98 11

info@skyriseplatform.com

skyriseplatform.com

İhlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul



Ask on WhatsApp