

SCISSOR LIFT

1412 (4647).1414 PLUS (4655 PLUS)

Electric Scissor Lift

MANUFACTURER · SINOBOOM

+90 216 999 95 99

info@skyriseplatform.com

skyriseplatform.com

İhlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul



Ask on WhatsApp

ELECTRIC SCISSOR LIFTS - HYDRAULIC DRIVE

1412 (4647)/1414 PLUS (4655 PLUS)

Compliant with CE/ANSI/CSA/KCS/EAC standards

PRODUCT HIGHLIGHTS

Efficient and Environmentally Friendly

- Higher work efficiency
- Environmental protection, zero emissions

Reduced Maintenance Costs

- The short design of sliding rail makes debris easy to clean
- Rapid convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts and components

Reliable Performance

- New wide scissor design, for a more stable working-at-height experience
- Bumper rail and indented sliding rail designed for anti-scratch

Standard Features		
2WD×2WS	Maintenance-free battery	Fault diagnosis system
Non-marking tires	Proportional control	Emergency lowering system
Emergency stop	Electrophoretic painting	Tilt protection system
Flashing beacon	Forklift pockets and lifting points	Overload sensing system
Foldable guardrail	Automatic pothole protection	Manual storage box
Drivable at full height	Bumper rails	Auto braking system
Horn & buzzer		
Options & Accessories		
RCBO	AC power to platform	Platform work light
Footswitch	Overhead anti-collision device	Telematics-ready connector
Lithium battery		

SINOBOOM™

PARTNERS IN ACCESS™

SINOBOOM.COM | SALES@SINOBOOM.COM




NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

ELECTRIC SCISSOR LIFTS - HYDRAULIC DRIVE

1412 (4647)/1414 PLUS (4655 PLUS)

Compliant with CE/ANSI/CSA/KCS/EAC standards

Model	1412 (4647)	1414 Plus (4655 Plus)
Dimensions		
Max Working Height (Indoor/Outdoor)	15.8 m (51'10")	15.8 m/10.5 m (51'10"/34'5.4")
A Max Platform Height (Indoor/Outdoor)	13.8 m (45'3")	13.8 m/8.5 m (45'3"/27'10.6")
B Max Horizontal Extension	0.9 m (3')	0.9 m (3')
C Length-Stowed	2.78 m (9')	2.78 m (9')
D Width-Stowed	1.27 m (4'2")	1.41 m (4'7")
E Height-Stowed (Rail Folded)	1.96 m (6'5")	1.98 m (6'6")
E Height-Stowed (Rail Unfolded)	2.6 m (8'6")	2.6 m (8'6")
F Wheelbase	2.22 m (7'3")	2.22 m (7'3")
Ground Clearance (Pothole Guard Stowed)	0.1 m (4")	0.95 m (3.74")
Ground Clearance (Pothole Guard Deployed)	0.025 m (0.98")	0.025 m (0.98")
Platform Size (L×W×H)	2.64 m×1.15 m×1.1 m (8'8"×3'9"×3'7")	2.64 m×1.3 m×1.1 m (8'8"×4'3"×3'7")
Performance		
Platform Capacity	227 kg (500 lbs)	350 kg (772 lbs)
Extension Platform Capacity	120 kg (265 lbs)	120 kg (265 lbs)
Platform Allowable Occupants (Indoor/Outdoor)	2 Persons (Indoor Only)	2 Persons/1 Person
Drive Speed (Stowed)	0~3.2 km/h (0~2mph)	0~3.2 km/h (0~2 mph)
Drive-Speed (Raised)	0~0.8 km/h (0~0.5mph)	0~0.8 km/h (0~0.5 mph)
Lift Time (Unloaded)	83 s~92 s	75 s~85 s
Lower Time (Unloaded)	55 s~65 s	55 s~63 s
Gradeability	25%	25%
Max Allowable Inclination (Front to Back/Side to Side)	3° /1.5°	3° /1.5°
Turning Radius (Inside/Outside)	0/2.64 m (0/8'8")	0/2.64 m (0/8'8")
Tire Size/Type	380×125 mm (15×5") /solid	380×125 mm (15×5") /solid
Power		
Drive×Steer	2 WD×2 WS	2 WD×2 WS
Power Source (V/kW)	24 V DC /4.5 kW	24 V DC /4.5 kW
Hydraulic Tank Capacity	15 L (3.3 gal (UK)/4 gal (US))	15 L (3.3 gal (UK)/4 gal (US))
Battery	24 V,280 Ah (Lead acid battery) 25.6 V,200 Ah (Lithium battery)	24 V,280 Ah (Lead acid battery) 25.6 V,200 Ah (Lithium battery)
Charger (Input/Output)	100~240V AC/30A	100~240V AC/30A
Weight		
Weight (Indoor/Outdoor)	3,360 kg (7,409 lbs) (Indoor Only)	3,560 kg (7,848 lbs)
Standards Compliance	CE/ANSI/CSA/EAC/KCS	CE/ANSI/CSA/EAC



We reserve the right to make specification. The above represents the current specifications at time of publications. 10. 2025

At height, you're safe with us

A large hire fleet of scissor, articulated, telescopic, vertical mast, trailer-mounted, tracked and truck-mounted platforms, delivered fully documented and well maintained. Let us help you choose the right machine.

- ✓ Free site survey and machine selection
- ✓ Periodic inspection and CE paperwork
- ✓ Operator training
- ✓ Transport and delivery across Türkiye
- ✓ Maintenance and on-site service throughout the hire
- ✓ 24/7 on-site support line

1,500+

corporate clients

CE-marked

inspected delivery

Across Türkiye

transport

24/7

on-site support

CONTACT

+90 216 999 95 99

WhatsApp +90 536 915 98 11

info@skyriseplatform.com

skyriseplatform.com

İhlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul



Ask on WhatsApp