

EKLEMLİ PLATFORM

AR24JE(AR80JE)

Akülü eklemli platform

ÜRETİCİ · LGMG

+90 216 999 95 99

info@skyriseplatform.com

skyriseplatform.com

İhlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul



WhatsApp ile sor

LGMG

AR24JE

ARTICULATING BOOM LIFT

- Lithium battery powered, low noise, zero-emission, maintenance-free, and high-capacity.
- Axle-integrated four-wheel drive system, with strong power and smooth transmission.
- Three steering modes: front-wheel, crab and four wheel steering, to meet the demand of operations in narrow space.
- Realize all-round aerial working through booms compound action.
- Full time floating to ensure driving safety.
- Higher anti-torsional strength frame to satisfy container transportation conditions.



LGMG Electric - Articulating Boom Lift

SPECIFICATIONS

MODELS	AR24JE (AR80JE)	
Measurements	Metric	Imperial
Work Height Max.	26.6m	87'3"
Platform Height Max.	24.6m	80'9"
Horizontal Outreach	18m	59'1"
Up and Over Height	8.83m	28'11"
Platform Length	2.44m	8'
Platform Width	0.9m	2'11"
Ⓐ Stowed Length	11.6m	36'1"
Length-Transport (jib tucked)	9.07m	29'9"
Ⓑ Overall Width	2.5m	8'2"
Ⓒ Stowed Height	2.83m	9'3"
Height-Transport	3.36m	11'
Ⓓ Wheelbase	2.85m	9'4"
Ⓔ Ground Clearance	0.4m	1'4"

PRODUCTIVITY

Platform Capacity (unrestricted)	250kg	551 lbs
Platform Capacity (restricted)	350kg	772 lbs
Max. Platform Occupancy	2 (unrestricted) / 3 (restricted)	
Turntable Rotation	360°	
Drive Speed-Stowed	5km/h	3.1mph
Drive Speed-Raised	0.8km/h	0.5mph
Gradeability	45%	
Max. Wind Speed	12.5m/s	28mph
Turning Radius-Inside	2.04m	6'8"
Turning Radius-Outside	4.13m	13'7"
Max.Slope	5°/5°	
Tires Type	Foam-filled non-marking	
Tires Models	15-625	

POWER

Power Source	80V 460Ah	
--------------	-----------	--

HYDRAULIC SYSTEM

Hydraulic Oil Volume	105L	27.7gal
----------------------	------	---------

WEIGHT




Machine Weight	17,300kg	38,139 lbs
----------------	----------	------------

STANDARD FEATURES

Proportional control	Emergency stop device
Horn/Hour meter	Auto-leveling platform
Full-height drive	Anti-collision protection
Flashing beacons	Over tilt protection system
Cylinder bellows	Platform control cover
Oscillating axle	Overload sensing system
Platform tool box	Intelligent diagnostic system
Telematics connector	Foam-filled non-marking tires

OPTIONAL

Telematics	Solid tires
AC power to platform	Solid non-marking tires
Half-height mesh platform	Foam-filled tires
Auxiliary rail	Biodegradable hydraulic oil



Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.

LINGONG HEAVY MACHINERY CO., LTD.

Address: No. 2676, Kejia Road, Jinan, Shandong, China
Email: sales@lmg.com.cn Tel: +86 531 6787 9283

LGMG Europe B.V.

Address: Donker Duyvisweg 301, 3316 BL Dordrecht, The Netherlands
Email: sales@lmggeurope.com Tel: +31 850 642 777

LGMG North America Inc.

Address: 4105 Live Oak Drive, Suite 100, The Colony, Texas 75056 United States
Email: sales@lmgna.com Tel: +1 833 288 5464

www.lmgglifts.com



LGMG
RELIABILITY IN ACTION

Yükseklerde bizimle güvendesiniz

Makaslı, eklemli, teleskopik, dikey, çekilebilir, paletli ve araçüstü platformlardan oluşan geniş kiralık filo; belgeli ve bakımlı olarak teslim edilir. İhtiyacınıza uygun makineyi birlikte seçelim.

- ✓ Ücretsiz keşif ve makine seçimi
- ✓ Periyodik kontrol ve CE evrakları
- ✓ Operatör eğitimi
- ✓ Türkiye geneli nakliye ve teslimat
- ✓ Kiralama boyunca bakım ve yerinde servis
- ✓ 7/24 saha destek hattı

1.500+

kurumsal müşteri

CE belgeli

kontrollü teslimat

Türkiye geneli

nakliye

7/24

saha desteği

İLETİŞİM

+90 216 999 95 99

WhatsApp +90 536 915 98 11

info@skyriseplatform.com

skyriseplatform.com

İhlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul



WhatsApp ile sor