SKYRISE PLATFORM

TEKNİK VERİ SAYFASI

MAKASLI PLATFORM

S4046EII

Akülü makaslı platform

ÜRETİCİ · LGMG

+90 216 999 95 99

info@skyriseplatform.com

skyriseplatform.com

Ihlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul

WhatsApp ile sor

LGMG
S4046E II

ELECTRIC MOTOR DRIVE SCISSOR LIFT

- Large lower control panel
- Entire range designed for indoor and outdoor use
- Universal key components
- More convenient to maintain
- Optional lithium battery for the entire product range

LGMG ELECTRIC MOTOR DRIVE SCISSOR LIFT

SPECIFICATIONS

MODELS	S4046EII (S1212EII)	
Measurements	Imperial	Metric
Work Height Max.	45'11"/31'2" (in/out)	14/9.5m (in/out)
Ⓐ Platform Height-Raised	39'4"/24'7" (in/out)	12/7.5m (in/out)
Ⓑ Platform Length	7'5"	2.26m
Ⓒ Platform Width	3'8"	1.12m
Ⓓ Overall Length	8'2"	2.49m
Ⓔ Overall Width	3'10"	1.18m
Ⓕ Overall Height-Guardrails Up	8'8"	2.63m
Ⓖ Overall Height-Guardrails Down	5'11"	1.8m
Ⓗ Extension Deck	2'11"	0.9m
Ⓘ Wheelbase	6'1"	1.85m
Ground Clearance(Stowed/Raised)	4"/1"	100/20mm
PRODUCTIVITY		
Max. Platform Occupants	2 (in) / 1(out)	
Platform Capacity	705 lbs	320kg
Platform Capacity-Extension Deck	265 lbs	120kg
Drive Height	Full Height	
Gradeability-Stowed	25%	
Min. Turning Radius	8'	2.45m
Raise/Lower Speed	65s / 60s	
Brakes	Front-wheel Brake	
Drive Mode	4x2	
Tire Type	Solid Non-marking	
Tire Size	15"x5"	380x130mm
Ground Pressure, Tyres	185.2 psi	1,277 kPa
POWER		
Power Source	24V (4x12V),300Ah,FLA	
Power Source	24V (4x6V),226Ah,AGM	
HYDRAULIC SYSTEM		
Hydraulic Oil Capacity	6.1gal	23L
WEIGHT		
Machine Weight	6,548 lbs	2,970kg

STANDARD FEATURES	
Proportional control	Indoor and outdoor rated
Foldable guardrail	Emergency stop device
Manual brake release	Swing-out component tray
Emergency descent	Tilt alarm with lift cut-out
Pothole guard	Overload sensing system
Self-lock entry gate	Descent alarm with flashing beacon
All motions alarm	Intelligent diagnostic system
Full-height drive	Solid non-marking tires

OPTIONAL	
AC power to platform	Anti-collision protection
Voice alarm system	Maintenance-free battery
Telematics	Biodegradable hydraulic oil



Please contact LGMG or a local dealer for more details.
LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.

LGMG North America Inc.
Address: 4105 Live Oak Drive, Suite 100, The Colony, Texas 75056 United States
Email: sales@lgmgna.com Tel: +1 833 288 5464
www.lgmgna.com

LGMG
RELIABILITY IN ACTION

SKYRISE PLATFORM

Yükseklerde bizimle güvendesiniz

Makaslı, eklemli, teleskopik, dikey, çekilebilir, paletli ve araçüstü platformlardan oluşan geniş kiralık filo; belgeli ve bakımlı olarak teslim edilir. İhtiyacınıza uygun makineyi birlikte seçelim.

- ✓ Ücretsiz keşif ve makine seçimi
- ✓ Periyodik kontrol ve CE evrakları
- ✓ Operatör eğitimi
- ✓ Türkiye geneli nakliye ve teslimat
- ✓ Kiralama boyunca bakım ve yerinde servis
- ✓ 7/24 saha destek hattı

1.500+	CE belgeli	Türkiye geneli	7/24
kurumsal müşteri	kontrollü teslimat	nakliye	saha desteği

İLETİŞİM

+90 216 999 95 99

WhatsApp +90 536 915 98 11

info@skyriseplatform.com

skyriseplatform.com

Ihlamurkuyu Mah. Şendal Sok. No: 2 · Ümraniye / İstanbul

WhatsApp ile sor

Bu dokümanın 2–3. sayfaları LGMG tarafından yayımlanan teknik veri sayfasıdır; içeriğine müdahale edilmemiştir. Kapak ve arka kapak Skyrise Platform tarafından eklenmiştir. Teknik değerler bilgilendirme amaçlıdır; üretici önceden haber vermeksizin değişiklik yapabilir.